

KYDEX® Sheet with Microban® Antimicrobial Protection MSDS - 108

Section 1: Chemical Product and Company Identification

Product/Chemical Name: KYDEX® with Microban® Antimicrobial Product Protection thermoplastic sheet; acrylic/PVC alloy

Other Designations: Mixture of polyvinyl chloride, chlorinated polyvinyl chloride, acrylic polymer, processing aids, impact modifiers, heat stabilizers, lubricants, and pigments

General Use: Thermoforming

Manufacturer: KYDEX, LLC, 6685 Low Street, Bloomsburg, PA 17815, PHONE 570.387.6997, FAX 570.387.8722

Emergency Phone Numbers: 570.387.6997. For transportation emergencies call CHEMTREC at 800.424.9300.

Section 2: Composition / Information on Ingredients

Ingredient Name	CAS Number	% wt
Polyvinyl chloride; ethene, chloro-homopolymer	9002-86-2	0-99
Chlorinated polyvinyl chloride	68648-82-8	0-99
Mixture of processing aids, impact modifiers, heat stabilizers, lubricants and pigments	TRADE SECRET	2-50
Organotin	TRADE SECRET	0.1-3

Section 3: Hazards Identification

Emergency Overview:

Kydex® with Microban® thermoplastic sheet, rigid plastic sheet, is in general a non-hazardous polymeric material and does not present any serious hazards during its normal handling and use. As with any material; however, there are guidelines that should be followed in an emergency situation. If dust or vapors are inhaled, get to well ventilated area. If skin or eyes are irritated, flush with water for 15 minutes.

HMIS	
H	1
F	1
R	0
PPE†	
†Sec. 8	

Potential Health Effects:

Primary Entry Routes: Inhalation, skin/eyes, ingestion (vapors if burned or dust from machining the sheet)

Target Organs: Respiratory system, eyes

Acute Effects:

Inhalation: Prolonged inhalation of dust from cutting or machining the plastic sheet may cause nose, throat and upper respiratory tract irritation. Excessive heating may lead to decomposition with the release of hydrogen chloride which could cause irritation to upper respiratory tract.

Eye: Excessive heating may lead to decomposition with the release of hydrogen chloride which could cause irritation of eyes

Skin: Dust from cutting and machining may be irritating to skin.

Ingestion: Not a likely route of exposure

Carcinogenicity: IARC, NTP, and OSHA do not list KYDEX® sheet as a carcinogen.

Medical Conditions Aggravated by Long-Term Exposure: Not known

Chronic Effects: Not known

KYDEX, LLC

ISO 9001 and 14001 Certified

Customer Service

6685 Low St, Bloomsburg, PA 17815 USA
Phone: 800.325.3133, +1.570.389.5810
Outside the US: +1.570.389.5814
Fax: 800.452.0155, +1.570.387.7786
Email: info@kydex.com

Technical Service

Phone: 800.682.8758 ext. 581
Fax: +1.570.387.8722
Outside the US: +1.570.387.6997 ext. 581

www.kydex.com

KYDEX® Sheet with Microban® Antimicrobial Protection MSDS - 108

Section 4: First Aid Measures

Inhalation: If irritation occurs from dust or vapors from excessive heating, move to a well-ventilated area; if irritation persists, consult a physician.
Eye Contact: If irritation occurs from dust or vapors from excessive heating, flush eyes with large amounts of water for at least 15 minutes; if irritation persists, consult a physician.
Skin Contact: Cool skin rapidly with cold water after contact with hot polymer. Wash off immediately with soap and plenty of water. Consult a physician.
Ingestion: Not a likely route of exposure
Notes to Physician: None
Special Precautions/Procedures: None

Section 5: Fire-Fighting Measures

Flash Point: 390°C (735°F)
Autoignition Temperature: 454°C (849°F)
Explosive Limits:
 LEL: Not available
 UEL: Not available



Flammability Classification: Not flammable
Extinguishing Media: Water, carbon dioxide, dry chemical or foam
Unusual Fire or Exponion Hazards: Polyvinyl chloride-based material will NOT continue to burn after ignition without an external heat source. When burning, or at temperatures above 425°F, slow evolution of hydrogen chloride could occur.
Hazardous Combustion Products: Hydrogen chloride, carbon monoxide, carbon dioxide
 NOTE: Hydrogen chloride is detectable by its sharp pungent odor in concentrations as low as 1 PPM. Low concentrations (< 50 PPM) are not harmful in short-term exposures but do provide excellent warning properties by causing coughing or irritation. Because the protective response is so strong, humans rarely submit to damaging concentrations -- instead there is an unmistakable urge to leave the area. Repeated or prolonged exposure to high concentrations can cause eye and respiratory damage.
Fire-Fighting Instructions: Keep unauthorized personnel removed.
Fire-Fighting Equipment: Because fire may produce toxic thermal decomposition products, wear a self-contained breathing apparatus (SCBA) with a full face piece operated in pressure-demand or positive-pressure mode.

Section 6: Accidental Release Measures

Spill /Leak Procedures: Not applicable. KYDEX® with Microban® sheets will not spill or leak; it is solid; however, dust from machining the product may leak or spill.
Small Spills: If dust or powder from cutting and machining the plastic sheet is spilled, vacuum or sweep up and place in containers for recovery or disposal.
Large Spills: If dust or powder from cutting and machining the plastic sheet is spilled, vacuum or sweep up and place in containers for recovery or disposal.
Containment: Not Applicable
Cleanup: Vacuum or sweep up and place in containers for recovery or disposal.
Regulatory Requirements: Follow applicable OSHA regulations (29 CFR 1910.120).

KYDEX, LLC
 ISO 9001 and 14001 Certified

Customer Service
 6685 Low St, Bloomsburg, PA 17815 USA
 Phone: 800.325.3133, +1.570.389.5810
 Outside the US: +1.570.389.5814
 Fax: 800.452.0155, +1.570.387.7786
 Email: info@kydex.com

Technical Service
 Phone: 800.682.8758 ext. 581
 Fax: +1.570.387.8722
 Outside the US: +1.570.387.6997 ext. 581

www.kydex.com

KYDEX® Sheet with Microban® Antimicrobial Protection MSDS - 108

Section 7: Handling and Storage

Handling Precautions: Dust levels should be kept below respiratory dust concentrations of 5 mg/m³. Take proper care when moving, loading, or unloading. Electrostatic charge may build up during handling; grounding of equipment is recommended.

Storage Requirements: Store in a dry area below 100°F (37.7°C).

Regulatory Requirements: KYDEX® or Vinyloy™ sheets are not regulated.

Section 8: Accidental Release Measures

Ingredient	OSHA PEL		AGGIH TLV	
	TWA	STEL	TWA	STEL
Polyvinyl chloride	15mg/m ³	none estab.	Particles Not Otherwise Classified: 10 mg/m ³	none estab.
Chlorinated polyvinyl chloride	15mg/m ³	none estab.	Particles Not Otherwise Classified: 10 mg/m ³	none estab.
Organotin	0.1 mg/m ³	none estab.	0.1 mg/m ³	0.2 mg/m ³
Titanium dioxide	15 mg/m ³	none estab.	10 mg/m ³	none estab.

Engineering Controls: Maintain levels of airborne contaminants below exposure levels by controlling general and local room ventilation in areas where machining, cutting or thermoforming occurs. Ground equipment to prevent build up of electrostatic charge.

Ventilation: Provide general or local exhaust ventilation systems to maintain airborne concentrations below OSHA PELs (Sec.2). Local exhaust ventilation is preferred because it prevents contaminant dispersion into the work area by controlling it at its source.

Administrative Controls: None

Respiratory Protection: Seek professional advice prior to respirator selection and use. Follow OSHA respirator regulations (29 CFR 1910.134) and, if necessary, wear a MSHA/NIOSH-approved respirator. Select respirator based on its suitability to provide adequate worker protection for given working conditions, level of airborne contamination, and presence of sufficient oxygen. Warning! Air-purifying respirators do not protect workers in oxygen-deficient atmospheres. If respirators are used, OSHA requires a written respiratory protection program that includes at least: medical certification, training, fit testing, periodic environmental monitoring, maintenance, inspection, cleaning, and convenient, sanitary storage areas.

Protective Clothing/Equipment: Wear protective eyeglasses or chemical safety goggles, per OSHA eye- and face-protection regulations (29 CFR 1910.133). Contact lenses are not eye protective devices. Appropriate eye protection must be worn instead of, or in conjunction with contact lenses.

Safety Stations: Make emergency eyewash stations, quick-drench showers, and washing facilities available in work area.

Contaminated Equipment: Not applicable

KYDEX, LLC

ISO 9001 and 14001 Certified

Customer Service

6685 Low St, Bloomsburg, PA 17815 USA
Phone: 800.325.3133, +1.570.389.5810
Outside the US: +1.570.389.5814
Fax: 800.452.0155, +1.570.387.7786
Email: info@kydex.com

Technical Service

Phone: 800.682.8758 ext. 581
Fax: +1.570.387.8722
Outside the US: +1.570.387.6997 ext. 581

www.kydex.com

KYDEX® Sheet with Microban® Antimicrobial Protection MSDS - 108

Section 9: Physical and Chemical Properties

Physical State: Solid
Appearance and Odor: Opaque plastic sheets; none or slight odor
Odor Threshold: Not available
Vapor Pressure: Not available
Vapor Density (Air=1): Not available
Formula Weight: Not available (Mix)
Density: 1.3-1.5 g/cc
Specific Gravity (H₂O=1, at 4 °C): 1.3-1.5
pH: Not available

Water Solubility: Negligible
Other Solubilities: Tetrahydrofuran
Boiling Point: Not available
Freezing Point: Not available
Viscosity: Not available (solid)
Refractive Index: Not available (opaque)
Surface Tension: Not available
% Volatile: Not available
Evaporation Rate: Not available

Section 10: Stability and Reactivity

Stability: KYDEX® with Microban® sheets are stable at room temperature under normal storage and handling conditions.
Polymerization: Hazardous polymerization WILL NOT occur.
Chemical Incompatibilities: Polyvinyl chloride-based materials should not come in contact with acetal or acetal polymers in elevated temperature processing equipment. The two materials are not compatible and will react in violent decomposition when mixed under conditions of heat and pressure.
Conditions to Avoid: Avoid temperatures of 218.3°C (425°F) and above.
Hazardous Decomposition Products: Carbon monoxide, carbon dioxide, hydrogen chloride.

Section 11: Toxicological Information

Toxicity Data:*
Eye Effects: Possible irritation due to dust particles.
Accute Inhalation Effects: Polyvinyl chloride [PVC]: Rats and guinea pigs exposed continuously to PVC dust for 24 hrs/day for periods varying from 2-7 months were found to have extensive lung damage. In rats, inhalation of fumes from heated PVC produced interstitial edema as well as focal, bronchial and intraveolar hemorrhage.
Accute Oral Effects: Not known
Chronic Effects: Not known
Carcinogenicity: KYDEX® sheet is not a carcinogen
Mutagenicity: Not known
Teratogenicity: Not known
** See NIOSH and RTECS for additional toxicity data.*

KYDEX, LLC

ISO 9001 and 14001 Certified

Customer Service

6685 Low St, Bloomsburg, PA 17815 USA
 Phone: 800.325.3133, +1.570.389.5810
 Outside the US: +1.570.389.5814
 Fax: 800.452.0155, +1.570.387.7786
 Email: info@kydex.com

Technical Service

Phone: 800.682.8758 ext. 581
 Fax: +1.570.387.8722
 Outside the US: +1.570.387.6997 ext. 581

www.kydex.com

KYDEX® Sheet with Microban® Antimicrobial Protection MSDS - 108

Section 12: Ecological Information

No ecological data available.

Section 13: Disposal Considerations

Wastes can be landfilled. Dispose of in accordance with federal, state, and local regulations.

Section 14: Transport Information

DOT Transportation Data (49 CFR 172.101):

Shipping Name: KYDEX sheet

Shipping Symbols: None

Hazard Class: Not regulated

ID No.: Not applicable

Packing Group: Not applicable

Label: Not applicable

Special Provisions (172.102): None

Packaging Authorizations: None

Quantity Limitations: None

Vessel Stowage Requirements: None

Section 15: Regulatory Information

EPA Regulations:

RCRA Hazardous Waste Number: Not listed (40 CFR 261.33)

CERCLA Hazardous Substance (40 CFR 302.4) unlisted specific per RCRA, Sec. 3001; CWA, Sec. 311 (b)(4); CWA, Sec. 307(a), CAA, Sec. 112

CERCLA Reportable Quantity: None

SARA /Title III Hazard Categories:

Immediate (Acute) Health: NO

Delayed (Chronic) Health: NO

Fire Hazard: NO

Reactive Hazard: NO

Sudden Release of Pressure: NO

OSHA Regulations:

Air Contaminant (29 CFR 1910.1000, Table Z-1, Z-1-A): Not listed

OSHA Standard (29 CFR 1910.1200) requires that information be provided to employees regarding the hazards of chemicals by means of a hazard communication program including labeling, material safety data sheets, training and access to written records. We request that you, and it is your legal duty to make all information in the Material Safety Data Sheet available to your employees.

State Regulations:

New Jersey Workplace Hazardous Substance List: Chlorinated polyvinyl chloride, organotin compound, modifier and lubricant, titanium dioxide

Pennsylvania Right to Know Act: Chlorinated polyvinyl chloride, organotin compound, modifier, lubricant

KYDEX, LLC

ISO 9001 and 14001 Certified

Customer Service

6685 Low St, Bloomsburg, PA 17815 USA

Phone: 800.325.3133, +1.570.389.5810

Outside the US: +1.570.389.5814

Fax: 800.452.0155, +1.570.387.7786

Email: info@kydex.com

Technical Service

Phone: 800.682.8758 ext. 581

Fax: +1.570.387.8722

Outside the US: +1.570.387.6997 ext. 581

www.kydex.com

Because we cannot anticipate or control the many different conditions under which this information and our products may be used, we do not guarantee the applicability of the accuracy of this information or the suitability of our products in any given situation. Users should conduct their own tests to determine the suitability of each product for their particular purposes. Data in the physical property table represents typical values and are to serve only as a guide for engineering design. Results are obtained from specimens under ideal laboratory conditions. Right to change physical properties as a result of technical progress is reserved. THE PRODUCTS DISCUSSED ARE SOLD WITHOUT WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE, EITHER EXPRESSED OR IMPLIED, EXCEPT AS PROVIDED IN OUR STANDARD TERMS AND CONDITIONS OF SALE. Buyer assumes all responsibility for loss or damage arising from the handling and use of our products, whether done in accordance with directions or not. In no event shall the supplier or the manufacturer be liable for incidental or consequential damages. Also, statements concerning the possible use of our products are not intended as recommendations to use our products in the infringement of any patent. Consult local code and regulatory agencies for specific requirements regarding code compliance, transporting, processing, recycling and disposal of our product. Product not intended for use as a heat resistant surface. Texture, product grade and other conditions may cause variations in appearance.

This information supersedes all previously published data.